



SEPTIC TANKS
RETAINING WALLS
MANHOLES/CATCH BASINS

ORILLIA PRECAST CONCRETE LIMITED

1979 S. Sparrow Lake Rd., Severn Bridge, ON P0E 1N0
Tel: 705-689-8428 Fax: 705-689-1565
Email: info@orilliaprecast.com www.orilliaprecast.com

OPC-MANHOLE

June 2, 2008

48" I.D. MANHOLE

SPECIFICATIONS:

Manufactured to ASTM-C478.

Concrete strength – Min. 4650 psi (32 MPa)

Reinforcing – 4x4 – 6/6 welded wire mesh

Inside Diameter – 48" (1200mm) with 5" (128 mm) wall thickness

Weights: - Riser sections - Approx. 845 lb/ft. (1339 kg./m.)
- 58" dia. Base - Approx. 1630 lb. (738 kg.)
- 58" dia. Flat top - Approx. 1536 lb. (697 kg.)
- Tapered top - Approx. 3715 lb. (1685 kg.)

Notes:

Base & Riser sections available in 1' to 6' heights, in 12" increments.

Custom sizes & locations for pipe holes.

Grade rings available in 2" and 3" sizes.

Cast iron frames & covers available.

Mastic or neoprene gaskets available.

Monolithic bases and extra ladders also available.

