



SEPTIC TANKS
RETAINING WALLS
BUILDING SYSTEMS

ORILLIA PRECAST CONCRETE LIMITED

1979 S. Sparrow Lake Rd., Severn Bridge, ON P0E 1N0
Tel: 705-689-8428 Fax: 705-689-1565
Email: info@orilliaprecast.com www.orilliaprecast.com

OPC-PC

PUMP TANKS



36" I.D. Pump Chamber - 30" H - 70 gal.
- 45" H - 121 gal.
- 60" H - 175 gal.

Pump Chamber lids - 41" O.D. - 6" H
c/w concrete inspection covers
optional plastic inspection covers

250 - 64" L x 41" W x 45" H - 38" Invert
400 - 76" L x 62" W x 45" H - 35" Invert
500 - 96" L x 48" W x 48" H - 38" Invert
600 - 96" L x 48" W x 63" H - 50" Invert



SPECIFICATIONS

- Concrete strength – 4600 psi / 32 mpa (minimum)
- Steel Reinforced
- Access risers available
- Pump chamber weights: 30"H - 985 lb., 45"H - 1325 lb., 60"H - 2990 lb.
- Pump tank weights: 250 - 2640 lb., 400 - 6655 lb., 500 - 5280 lb., 600 - 9200 lb.