



SEPTIC TANKS, WELL TILES  
STEPS, RETAINING WALLS  
MANHOLES & CATCH BASINS  
BUILDING SYSTEMS

WELL TILES

**ORILLIA PRECAST CONCRETE LIMITED**

2085 S. Sparrow Lake Rd., Severn Bridge, ON P0E 1N0  
Tel: 705-689-8428 Fax: 705-689-1565  
Email: [info@orilliaprecast.com](mailto:info@orilliaprecast.com) [www.orilliaprecast.com](http://www.orilliaprecast.com)

---

---

## WELL TILES

---

---



---

## SPECIFICATIONS

---

**36" WELL TILES**

- Concrete strength – 4600 psi / 32 mpa (minimum)
- Total Wt. (approximate) 680 lbs / 309 kg Lid 415 lbs. /188 kg
- Dimensions 36" I.D. (41" O.D.)  
30" Hi  
60" Hi  
15" Hi  
Top 5 ½ " Hi

**48" WELL TILES**

- Total Wt. (approximate) 845lbs / 384 kg Lid 1335 lbs. / 606 kg
- Dimensions 48" I.D. (58" O.D.) 1' sections up to 6'  
Top 12" Hi  
Top with 36" tile adapter 24" Hi 1335 lbs / 995 kg

**30" WELL TILES**

- Total (approximate) 590 lbs / 268 kg Lid 285 lbs. /129 kg
- Dimensions 30 "I.D. (34.5" O.D.)  
30" Hi  
15" Hi  
Top 5 ½ " Hi